

FMU130

ADVANCED 3G TERMINAL WITH FLEXIBLE INPUTS CONFIGURATION

FMU130 is small and professional real-time tracking terminal with GNSS and 3G/GSM connectivity and backup battery. Device equipped with GNSS/Bluetooth and 3G modules, internal GNSS, 3G antennas, configurable digital, analogue inputs and digital outputs, negative input, impulse inputs. It is perfectly suitable for applications where location acquirement of remote objects is needed: fleet management, car rental companies, taxi companies, public transport, logistics companies, personal cars and so on.



USE CASES



LIGHT VEHICLES



HEAVY DUTY TRANSPORT



TRAILER TRACKING



REFRIGERATED TRANSPORT



INTERNATIONAL LOGISTICS



CAR SHARING



Module

Name	Quectel UC15-A/UC15-T or Quectel UG96, Teltonika TM2500
Technology	3G(UMTS/HSPA)/2G(GSM/GPRS)/GNSS/BLUETOOTH

GNSS

GNSS	GPS, GLONASS, GALILEO, BEIDOU, QZSS
Protocol compatible	NMEA, GGA, GGL, GSA, GSV, RMC, VTG
Receiver	Tracking: 33/99 acquisition channels
Tracking sensitivity	-110 dBm
Accuracy	< 3 m
Hot start	< 1 s
Warm start	< 25 s
Cold start	< 35 s

Cellular

Technology	UMTS/HSPA
2G bands	UC15-A: B5/B8/B3/B2 UC15-T: B5/B8/B3/B2 UG96: B5/B8/B3/B2
3G bands	UC15-A: B5/B2 UC15-T: B5/B1 UG96: B6/B5/B8/B2/B1
Data transfer	UC15: HSDPA: Max. 3.6Mbps (DL) UMTS: Max. 384Kbps (DL)/Max.384Kbps (UL) GPRS: Max. 85.6Kbps (DL)/Max. 85.6Kbps (UL) UG96: HSUPA: Max. 5.76Mbps UMTS: Max. 384Kbps (DL)/Max.384Kbps (UL) GPRS: Max. 107Kbps (DL)/Max.85.6Kbps (UL)
Data support	SMS (text/data)

Power

Input voltage range	10 - 30 V DC with overvoltage protection
Internal Back-up battery	170 mAh Li-Ion battery 3.7 V (0.63 Wh)

Bluetooth

Specification	4.0 + LE
Supported peripherals	Temperature and Humidity sensor, OBDII dongle, Inateck Barcode Scanner, Universal BLE sensors support

Physical specification

Dimensions 65 x 56.6 x 20.6 mm (L x W x H)

Weight 55 g

Operating environment

Operating temperature (without battery) -40 °C to +85 °C

Storage temperature (without battery) -40 °C to +85 °C

Operating humidity 5% to 95% non-condensing

Ingress Protection Rating IP41

Battery charge temperature 0 °C to +45 °C

Battery discharge temperature -20 °C to +60 °C

Battery storage temperature -20 °C to +45 °C for 1 month
-20 °C to +35 °C for 6 months

Interface

Digital Inputs 3

Negative Inputs 1 (Digital Input 2)

Impulse Inputs 2 (Digital Input 1, Digital Input 2)

Digital Outputs 3

Analog Inputs 2

CAN Adapter Inputs 1

1-Wire 1

GNSS antenna Internal High Gain

Cellular antenna Internal High Gain

USB 2.0 Micro-USB

LED indication 2 status LED lights

SIM Micro-SIM + eSIM

Memory 128MB internal flash memory

Features

Sensors Accelerometer

Scenarios Green Driving, Over Speeding detection, Jamming detection, GNSS Fuel Counter, DOUT Control Via Call, Excessive Idling detection, Immobilizer, iButton Read Notification, Unplug detection, Towing detection, Crash detection, Auto Geofence, Manual Geofence, Trip

Sleep modes GPS Sleep, Online Deep Sleep, Deep Sleep, Ultra Deep Sleep

Configuration and firmware update FOTA Web, FOTA, Teltonika Configurator (USB, Bluetooth), FMBT mobile application (Configuration)

SMS Configuration, Events, DOUT control, Debug

GPRS commands Configuration, DOUT control, Debug

Time Synchronization GNSS, NITZ, NTP

Fuel monitoring LLS (Analog), LV-CAN200, ALL-CAN300, CAN-CONTROL, OBDII dongle

Ignition detection Digital Input 1, Accelerometer, External Power Voltage, Engine RPM (CAN Adapters, OBDII dongle)

